

SERIES	SIZE	SI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(KPa)	TREAD.	TRAC.	TEMP.
65	205/65R16C	107/105	R	8	BSW	6.0	5.5 - 6.5	672	209	9.1	975	2150	925	2040	69	475	-	-	-
	215/65R16C	109/107	R	8	BSW	6.5	6.0 - 7.0	686	221	9.4	1030	2270	975	2150	69	475	-	-	-
	235/65R16C	115/113	R	8	BSW	7.0	6.5 - 7.5	712	140	9.4	1250	2680	1150	2535	69	475	-	-	-
70	195/70R15C	104/102	R	8	BSW	6.0	5.5 - 6.5	655	201	9.5	900	1985	850	1875	65	450	-	-	-
	205/70R15C	106/104	Q	8	BSW	6.0	5.5 - 6.5	669	209	9.5	950	2094	900	1984	65	450	-	-	-
	215/70R15C	109/107	R	8	BSW	6.5	6.0 - 7.0	683	221	9.5	1030	2277	975	2150	65	450	-	-	-
	225/70R15C	112/110	R	8	BSW	6.5	6.0 - 7.0	697	228	9.4	1120	2470	1060	2335	65	450	-	-	-
75	205/75R16C	110/108	R	8	BSW	5.5	5.0 - 6.0	714	203	9.1	1060	2335	1000	2205	69	475	-	-	-
	215/75R16C	113/111	R	8	BSW	6.0	5.5 - 6.5	728	216	9.4	1150	2535	1090	2405	69	475	-	-	-
	225/75R16C	116/114	R	8	BSW	6.0	5.5 - 6.5	744	223	9.4	1250	2755	1180	2600	69	475	-	-	-

