

SERIES	SIZE	SI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(KPa)	TREAD.	TRAC.	TEMP.
50	265/50R20	107	T	-	BSW	8.5	8.0-9.0	774	277	9.6	975	2150	-	-	44	300	540	A	B
55	275/55R20 XL	117	T	-	BSW	8.5	8.0-9.0	810	284	9.6	1285	2835	-	-	50	340	540	A	B
	285/55R20	115	T	-	BSW	9.0	8.5-9.5	822	297	9.6	1215	2680	-	-	44	300	540	A	B
60	265/60R18	110	T	-	BSW	8.0	7.5-8.5	775	272	9.6	1060	2335	-	-	44	300	540	A	B
	275/60R20	115	T	-	BSW	8.0	7.5-8.5	838	279	9.6	1215	2680	-	-	44	300	540	A	B
65	245/65R17	107	T	-	BSW	7.0	6.5-7.5	750	248	9.6	975	2150	-	-	44	300	540	A	B
	265/65R17	112	T	-	BSW	8.0	7.5-8.5	776	272	9.6	1120	2470	-	-	44	300	540	A	B
	275/65R18	116	S	-	BSW/OWL	8.0	7.5-8.5	815	279	9.6	1250	2755	-	-	44	300	540	A	B
70	LT265/70R17	121/118	S	10	BSW	8.0	7.5-8.5	804	272	12	1450	3195	1320	2910	80	550	-	-	-
	LT285/70R17	121/118	T	10	BSW	8.5	8.0-9.0	832	292	9.6	1459	3195	1320	2910	80	550	-	-	-
	235/70R16	106	T	-	BSW	7.0	6.5-7.5	736	240	9.6	950	2095	-	-	44	300	540	A	B
	245/70R16 XL	111	T	-	BSW	7.0	6.5-7.5	750	248	9.6	1090	2405	-	-	50	340	540	A	B
	245/70R17	110	T	-	BSW	7.0	6.5-7.5	776	248	9.6	1060	2335	-	-	44	300	540	A	B
	255/70R16	111	T	-	BSW	7.5	7.0-8.0	764	260	9.6	1090	2405	-	-	44	300	540	A	B
	265/70R16	112	T	-	BSW	8.0	7.5-8.5	778	272	9.6	1120	2470	-	-	44	300	540	A	B
	265/70R17	115	T	-	BSW	8.0	7.5-8.5	804	272	9.6	1215	2680	-	-	44	300	540	A	B
	265/70R18	116	T	-	BSW	8.0	7.5-8.5	829	272	9.6	1215	2755	-	-	44	300	540	A	B
75	LT225/75R16	115/112	S	10	BSW/OWL	6.0	5.5-6.5	744	223	11	1215	2680	1120	2470	80	550	-	-	-
	LT235/75R16	104/101	S	6	BSW/OWL	6.5	6.0-7.0	733	235	11	900	1985	825	1820	50	350	-	-	-
	LT245/75R16	120/116	S	10	BSW/OWL	7.0	6.5-7.5	774	248	12	1400	3085	1250	2755	80	550	-	-	-
	LT245/75R17	121/118	S	10	BSW	7.0	6.5-7.5	800	248	12.1	1450	3195	1320	2910	80	550	-	-	-
	LT265/75R16	123/120	S	10	BSW/OWL	7.5	7.0-8.0	804	267	12	1550	3415	1400	3085	80	550	-	-	-
	LT285/75R16	126/123	S	10	BSW	8.0	7.5-8.5	834	286	12.1	1700	3750	1550	3415	80	550	-	-	-
	235/75R15	105	T	-	BSW	6.5	6.0-7.0	733	235	9.6	925	2040	-	-	44	300	540	A	B
	245/75R16	111	T	-	BSW	7.0	6.5-7.5	774	248	9.6	1090	2405	-	-	44	300	540	A	B
265/75R16	116	T	-	BSW	7.5	7.0-8.0	804	267	9.6	1250	2755	-	-	44	300	540	A	B	
80	LT235/80R17	120/117	S	10	BSW	6.5	6.0-7.0	808	235	12.1	1400	3085	1285	2835	80	550	-	-	-
85	LT215/85R16	115/112	S	10	BSW/OWL	6.0	5.5-6.5	772	216	11	1215	2680	1120	2470	80	550	-	-	-
	LT235/88R16	120/116	S	10	BSW/OWL	6.5	6.0-7.0	806	235	12	1400	3085	1250	2755	80	550	-	-	-
	30X10.50R15LT	104	S	6	BSW/OWL	7.5	7.0-8.0	750	240	12	900	1985	-	-	50	350	-	-	-
	31X10.50R15LT	109	S	6	BSW/OWL	8.5	8.0-9.0	775	268	12	1030	2270	-	-	50	350	-	-	-
	35X12.5R17LT	121	S	10	BSW	10.0	9.5-10.5	877	318	12	1450	3195	-	-	65	450	-	-	-

